

UNITED STATES PATENT AND TRADEMARK OFFICE  
**CERTIFICATE OF CORRECTION**


PATENT NO. : 7,257,328 B2  
APPLICATION NO. : 09/735710  
DATED : August 14, 2007  
INVENTOR(S) : Levinson et al.

Page 1 of 5

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

**Drawings**

Sheet 4, replace Figure 5 with the figure depicted below, wherein Tone addr is relabeled **225-1** and "Test data generator" is renamed "Test signal generator"




Signed and Sealed this

Twenty-sixth Day of October, 2010

*David J. Kappos*


David J. Kappos  
Director of the United States Patent and Trademark Office

Sheet 7, replace Figure 8 with the figure depicted below, wherein "Test data generator" is renamed "Test signal generator" and Control logic Circuit is relabeled 227-1X




**FIG. 8**

Sheet 9, replace Figure 10 with the figure depicted below, wherein "Test data generator" is renamed "Test signal generator"



**FIG. 10**

Sheet 12, replace Figure 13 with the figure depicted below, wherein "Other Service" is renamed "Other Sources"



**FIG. 13**

**Column 5**

Line 24, after "optical", add [fiber]

**Column 7**

Line 64, after "ADC 202-1" add [(FIG. 4)]

Line 65, after "ADC 202-2" add [(FIG. 4)]

**Column 8**

Line 5, change "is" to --are--

Line 41, change "0for" to --0, for--

**Column 9**

Line 5, after "SERDES 206", add [(FIG. 4)]

Line 6, after "SERDES", add [206 (FIG. 4)]

Line 10, after "200", add [(FIG. 4)]

Line 15, after "200", add [(FIG. 4)]

**Column 10**

Line 13, after "227", add [(FIG. 5)]

Line 15, after "223-2", add [(FIG. 5)]

Line 19, after "227", add [(FIG. 5)]

Line 49, after "227", add [(FIG. 5)]

Line 53, after "229", add [(FIG. 5)]

**Column 10**

Line 54, after “227”, add [(FIG. 5)]

Line 59, after “229”, add [(FIG. 5)]

**Column 11**

Line 4, after “227”, add [(FIG. 5)]

Line 5, after “229”, add [(FIG. 5)]

Line 10, after “223”, add [(FIG. 5)]

Line 14, after “223”, add [(FIG. 5)]

Line 42, after “above,”, add [and in reference to FIGS. 4 and 5]

Line 66, after “laser”, add [diode]

**Column 12**

Line 44, change “The receiver 250” to --In FIG. 9, the receiver 250--

Line 51, after “106-2”, add [(FIG. 4)]

**Column 13**

Line 21, after “258”, add [(FIG. 9)]

Line 44, after “281”, add [(FIG. 10)]

Line 45, after “280-1”, add [(FIG. 10)]

Line 47, after “280-1”, add [(FIG. 10)]

Line 49, after “280-2”, add [(FIG. 10)]

Line 50, after “280-2”, add [(FIG. 10)]

Line 66, change “2801” to --280-1--

**Column 14**

Line 27, after “265”, add [(FIG. 9)]

Line 29, after “200”, add [(FIG. 4)]

Line 34, after “250”, add [(FIG. 9)]

Line 36, after “200”, add [(FIG. 4)]

Line 44, after “265”, add [(FIG. 9)]

Line 46, after “200”, add [(FIG. 4)]

Line 60, after “250”, add [(FIG. 9)]

Line 63, after “250”, add [(FIG. 9)]

**Column 15**

Line 7, after “250”, add [(FIG. 9)]

Line 21, after “250”, add [(FIG. 9)]

Line 39, after “250”, add [(FIG. 9)]

Line 43, change “test generator circuit” to --test signal generator--

**Column 16**

Line 1, after “223-2”, add [(FIG. 5)]

Line 7, change “2021” to --202-1--

Line 8, after “223-2”, add [(FIG. 5)]

Line 10, change “2231” to --223-1--

Line 12, change “The receiver 250” to --In FIG. 9, the receiver 250--

Line 13, after “210”, add [(FIG. 4)]

**Column 16**

Line 18, after “280-2”, add [(FIG. 10)]

Line 30, after “280-2”, add [(FIG. 10)]

Line 40, change “The sample clock” to --Referring back to FIGS. 9 and 10, the sample clock--

**Column 17**

Line 44, after “(TDM)”, add [334]

Line 47, after “202”, add [(FIG. 4)]

**Column 18**

Line 7, change “digital signal feeds” to --data feeds--

Line 28, change “314” to --340--

Line 28, change “314” to --340--

Line 34, change “314” to --340--

Line 45, change “service 314” to --sources 340--

Line 46, change “service 314” to --sources 340--

Line 47, change “service 314” to --sources 340--

Line 49, change “service 314” to --sources 340--

Line 50, after “hub”, add [330]

**Column 21**

Line 31, after “402”, add [(FIG. 14)]

Line 52, after “404”, add [(FIG. 14)]

Line 54, after “404-0”, add [(FIG. 14)]

Line 60, after “404-0”, add [(FIG. 14)]

**Column 23**

Line 67, after “203”, add [(FIG. 16)]

**Column 24**

Line 52, change “474” to --474-1--

Line 53, change “474” to --474-1--

Line 54, change “474” to --474-1--

Line 58, change “474” to --474-1--

Line 63, change “474” to --474-1--

**Column 25**

Line 1, change “474” to --474-1--

Line 4, after “438”, add [(FIG. 16)]

Line 5, after “laser”, add [diode]

Line 13, change “17” to --16--

Line 45, after “200”, add [(FIG. 4)]